

TruFlush Flushometer

An innovative flushometer for the global market.

SLOAN

SLOAN The TruFlush Flushometer is compatible with a wide variety of washdown and siphon jet fixtures.

Making a world of difference.

Commercial restrooms around the world are flushing large amounts of water down the drain. The commonly used valve simply opens and closes, wasting water with every flush.

As the leader in commercial water efficiency, and pioneer of the original flushometer in 1906, it's only natural that we aid in solving this global issue of water scarcity. Our design and engineering teams went to work to develop a truly innovative global flushometer.

The Sloan TruFlush Flushometer is an attractive, accurate, reliable, concealed flushometer that is simple to install, easy to maintain and perfect for any commercial application.

Designed and engineered for commercial restrooms.

Install the TruFlush Flushometer in any environment and see the savings.

Water savings with every flush.

With high-efficiency flush volumes, the TruFlush Flushometer delivers the prescribed volume of water each time. Compared to a metering valve, this saves water with every flush.

Accuracy with any water pressure.

Compared to the commonly used valve that simply opens and closes, the TruFlush reliably controls the amount of water used. Sloan's proven piston technology provides a consistent flush volume for pressures from 0.7 bars to 7 bars (10 psi to 100 psi).

Beautifully designed and built to last.

The corrosion-resistant wall plate is sleek and simple in design and engineered to perform in any environment. Sloan's innovative engineering, quality materials and expert workmanship produce a flushometer you can count on for years to come.

Multiple methods of activation.

The TruFlush Flushometer comes in two activation options: manual, with an easy to push button and sensor, with advanced infrared technology that delivers hygienic, hands-free performance.

Anatomy of the TruFlush Flushometer.

See Sloan's revolutionary patented technology.



1. Wall Plate & Button

The design is sleek, simple, vandal-resistant and built to last. Available in polished chrome and brushed stainless.*

4. Activation Assembly

The activation assembly is used to adjust the water flow rate and is easily accessible through the wall plate. The integrated aspirator reduces noise at shutoff.

2. Bracket

The bracket is easy to install with just three screws needed for mounting.

5. Piston

Sloan's proven piston technology is the heart of the flushometer and accurately controls the flush volume. Enhanced filtration is designed for even the harshest water conditions.

3. Safety Ring

During maintenance and installation, the safety ring securely locks the internal components in place.

6. Valve Body

The heavy-duty brass and corrosionresistant valve body houses the internal components and works with a variety of flush connections.

Easy to install. Easy to maintain.

Installation and maintenance of the TruFlush is simple, with the ability to shut off water and replace parts in minutes, all through the wall plate.



Quick and easy installation.

The TruFlush has a clean and compact valve body design, ideal for new construction or as a retrofit to most existing plumbing systems. The TruFlush is also compatible with a wide variety of washdown and siphon jet fixtures.



Fewer parts, fewer problems.

The TruFlush was designed with as few parts as possible, making maintenance a breeze. The parts are easily accessible through the wall plate and are designed to minimize the opportunity for leaking and worry.



Infinite applications.

The TruFlush is available in manual and sensor models, with varying flush volumes, and a wide variety of flush connections to fit the needs of your commercial restroom.

TruFlush Flushometer Product Line.

Manual





Polished Chrome (CP)

Brushed Stainless* (SF)

Model Number	Fixture Type	Flush Volume
TRF 156-1.1	Water Closet	High-Efficiency (4.0 Lpf/1.1 gpf)
TRF 156-1.28	Water Closet	High-Efficiency (4.8 Lpf/1.28 gpf)
TRF 156-1.6	Water Closet	Low Consumption (6.0 Lpf/1.6 gpf)
TRF196-0.125	Urinal	High-Efficiency (0.5 Lpf/0.125 gpf)
TRF 196-0.25	Urinal	High-Efficiency (1.0 Lpf/0.25 gpf)
TRF196-0.5	Urinal	High-Efficiency (1.9 Lpf/0.5 gpf)

Sensor-activated





Polished Chrome (CP)

Brushed Stainless* (SF)

Model Number	Fixture Type	Flush Volume
Battery with hardwired	doption	
TRF 8156-1.1	Water Closet	High-Efficiency (4.0 Lpf/1.1 gpf)
TRF 8156-1.28	Water Closet	High-Efficiency (4.8 Lpf/1.28 gpf)
TRF 8156-1.6	Water Closet	Low Consumption (6.0 Lpf/1.6 gpf)
TRF 8196-0.125	Urinal	High-Efficiency (0.5 Lpf/0.125 gpf)
TRF 8196-0.25	Urinal	High-Efficiency (1.0 Lpf/0.25 gpf)
TRF 8196-0.25	Urinal	High-Efficiency (1.0 Lpf/0.25 gpf)

*Brushed Stainless (SF) only available in select international markets.



Front Cover: TruFlush TRF-156 Manual Flushometer in Polished Chrome.

Back cover: TruFlush TRF-8156 Sensor Flushometer in Polished Chrome with ST-2469 Wall-mounted Water Closet and AER-DEC® AD-81000 in Corian® Sparkling Granita with custom vertical enclosure.



World Headquarters

10500 Seymour Avenue Franklin Park, IL 60131 U.S.A. 800.982.5839 sloan.com

Follow Sloan

f /sloanvalvecompany
✓ @sloan_valve
Ø @sloan_valve

/sloan_valve

 $in \ / {\rm sloan-valve-company}$

©2022 Sloan Valve Company. All Rights Reserved. TruFlush not available in USA or Canada.